

P/N: ARNGFFM224C8T-256

A-RAY 2242 NGFF M.2 C800 256GB

DESCRIPTION

C800 256GB is an SSD hard drive using a connection interface NGFF M.2 2242 controller. This is a SSD Commercial Series that delivers read/write speeds up to 550/500 MBps and Support TRIM, NCQ, S.M.A.R.T, ECC, Wear-leveling.

System Support: Windows XP/Win7/8/10/11, Mac OS , Linux, embedded operating systems used in control, measurement, and applications such as: Music server, Automation control....

Precautions:

[1] The speed was tested by A-RAY and for the reference only.

[2] 1GB=1,000,000,000 Bytes. In OS system, it would be displayed as 1,000,000,000 Bytes/1024/1024/1024 = 0.93GB

[3] Definition and conditions of TBW (Terabytes Written) are based on JEDEC standard

[4] Transmission speed will vary according to different hardware/software conditions, therefore the data can only use for basic reference.

NOTES:

[5] We reserve the right to modify product specifications without prior notice.

[6] Different devices may have a different best format for usage. It is recommended to format the device before use to ensure the correctness and the integrity of the SSD.

[7] (1): We can use any of the above driver ICs. Basically, they do not change the performance and basic specifications.

[8] (2): We may change any type of memory chip for any product line without notice.

SPECIFICATIONS

Series:	C800 Commercial Series
Model:	2242 NGFF M.2 C800 256GB
Capacity:	256GB
Performance Read/Write:	550/500 MBps
Interface:	NGFF M.2 2242
Controller: ⁽¹⁾	SMI: SM2258XT SMI: SM2259XT Phison: S11
NAND: ⁽²⁾	Intel/Micron 3D TLC Nandflash Original/Good Die
Support:	Support TRIM, NCQ, S.M.A.R.T, ECC, Wear-leveling
Support Computer:	- Desktop - Laptop - AIOs - Server - Industrial Computer - Commercial Computer - Consumer Computer
System Support:	Windows XP/Win7/8/10/11, Mac OS , Linux, embedded operating systems used in control, measurement, and applications such as: Music server, Automation control...
Operating Voltage:	3.3V
Dimensions:	42*22*3.2mm
Operating Temperature:	0 - 70°C
Storage Temperature:	-40 - 85°C
Humidity:	0°C ~ 50°C/5% ~ 95% RH, non-condensing
Warranty:	Lifetime warranty – 36 months
Quality Certification:	CE, FCC, ROHs