

P/N: ARNVMeM228S9T-128ANT

A-RAY 2280 NVMe M.2 S900 128GB

DESCRIPTION

S900 128GB is an SSD hard drive using a connection interface NVMe M.2 2280 controller. This is a SSD Strong Series that delivers read/write speeds up to 1600/550 MBps and Support TRIM, NCQ, S.M.A.R.T, ECC, Wear-leveling. System Support: Windows XP/Win7/8/10/11, Mac OS, Linux, embedded operating systems used in control, measurement, and applications such as: Music server, Automation control....

Precautions:

[1] The speed was tested by A-RAY and for the reference only.

[2] 1GB=1,000,000,000 Bytes. In OS system, it would be displayed as 1,000,000,000 Bytes/1024/1024/1024 = 0.93GB

[3] Definition and conditions of TBW (Terabytes Written) are based on JEDEC standard

[4] Transmission speed will vary according to different hardware/software conditions, therefore the data can only use for basic reference.

NOTES:

[5] We reserve the right to modify product specifications without prior notice.

[6] Different devices may have a different best format for usage. It is recommended to format the device before use to ensure the correctness and the integrity of the SSD.

[7] (1): We can use any of the above driver ICs. Basically, they do not change the performance and basic specifications.

[8] (2): We may change any type of memory chip for any product line without notice.

SPECIFICATIONS

| | |
|----------------------------|--|
| Series: | S900 Strong Series |
| Part Number: | ARNVMeM228S9T-128ANT |
| Capacity: | 128GB |
| Performance Read/Write: | 1600/550 MBps |
| Interface: | NVMe M.2 2280 |
| Controller: ⁽¹⁾ | SMI: SM2263XT |
| NAND: ⁽²⁾ | Intel/Micron 3D TLC Nandflash Original/Good Die |
| Support: | Support TRIM, NCQ, S.M.A.R.T, ECC, Wear-leveling |
| Support Computer: | <ul style="list-style-type: none"> - Desktop - Laptop - AIOs - Server - Industrial Computer - Commercial Computer - Consumer Computer |
| System Support: | Windows XP/Win7/8/10/11, Mac OS, Linux, embedded operating systems used in control, measurement, and applications such as: Music server, Automation control... |
| Operating Voltage: | 3.3V |
| Dimensions: | 80*22*3.2mm |
| Operating Temperature: | 0 - 70°C |
| Storage Temperature: | -40 - 85°C |
| Humidity: | 0°C ~ 50°C/5% ~ 95% RH, non-condensing |
| Warranty: | Lifetime warranty – 36 months |
| Quality Certification: | CE, FCC, ROHS |

